

P-9500Dv2 DMR DIGITAL MOBILE RADIO ASSOCIATION

Professional Digital Radio

Features

- TDMA Dual Slot Technology
- Digital/Analog Modes
- Call Digital Encryption
- Remote Stun/Kill, Activate, Revive
- High/Low Power Selectable
- Multi-call Modes
- Priority Channel Scan in Analog/Digital Modes
- User-defined Ring Tone and Vibration Alert
- Built-in CTCSS/DCS
- VOX

Specifications

- Frequency: 136-174MHz / 400-470MHz
- Channel Spacing: 12.5KHz/25KHz
- Channels: 16
- Output Power: VHF: 5W/1W, UHF: 4W/1W
- Operating Temperature: -30°C~+60°C
- Modulation: 12.5KHz(Data): 7K60FXD;
12.5KHz(Data & Voice): 7K60FXE
- Battery Pack: 2000mAh Li-po(DC7.4V)
- Provides 9 hours operating time (approx.)
(Typical operation with Tx (Hi): Rx: standby=5:5:90)
- Digital Sensitivity: -110dBm(BER≤ 1%);
-117dBm(BER≤ 5%)
- Adjacent Channel Selectivity: -50dB@12.5KHz
- Adjacent Channel Power: ≤ -60dB@12.5KHz
- Dimensions(W×H×D): 61× 135× 36mm
- Weight: 253g(With Belt Clip and Antenna)



Li-ion Battery



Antenna



Belt Clip



AC Adaptor



Desktop Charger