

ADESSO

WT-3100
WT-3200
Professional Transceiver



MAIN FEATURES

Output power: UHF 4W / VHF 5W
Freq. band: 400-470MHz / 136-174MHz
Encrypted programming software
ANI and PTT-ID
Side key assignment
Busy channel lock
DTMF
0-9 grades squelch level setting

ADESSO

WT-3100
WT-3200
Professional Transceiver



Output power: UHF 4W / VHF 5W
Freq. band: 400-470MHz / 136-174MHz
Encrypted programming software · ANI and PTT-ID
Side key assignment · Busy channel lock · DTMF
0-9 grades squelch level setting

Your local dealer

SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	VHF: 136~174MHz	RF Power	5W
	UHF: 400~470MHz	Modulate Mode	F3E
Operating Temperature	-25°C~+55°C	Max. Freq. Deviation	≤5KHz
Frequency Combination	Phase lock frequency synthesizer	Remain Wave Radiation	<-60dB
Frequency Stability	±2.5ppm	Transmitting Current	≤1000mA
Memory Channel	16 Channels	RECEIVE PART	
Working voltage	7.4V (Li-ion Battery)	Sensitivity	<0.25μV(12dB SINAD)
Antenna Impedance	50Ω	Squelch Sensitivity	<0.20μV
Operating Mode	Simplex of co-freq. or alien freq.	Audio Power output	≤1000mW
Dimension	113mm×55mm×32mm	Receiving Current	≤100mA
Weight	232g (Include Battery Pack)	Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.