ADESSO TREK WALKIE TALKIE



► Instruction Manual



Main Features

- Compact, lightweight but rugged design
- Wide LCD display with backlight
- 38 CTCSS tones & 83 DCS codes in TX and RX
- Buttons for the channel selection
- Knob for volume adjustment
- CALL key with 10 tones selectable
- Built-in LED flashlight
- Squelch tail elimination
- VOX for hands-free communications
- Monitor, channel scan
- Keypad lock, roger beep, battery save
- Fast charger and battery life up to 25 hours
- 2 pin jack for external microphone & speaker
- Standard micro USB port to recharge the battery

Contents

01	Chapter 1: Safety Information
01	Radio Care
01	Battery Care
03	Chapter 2: Radio Overview
03	Package Includes
03	At a Glance
05	Chapter 3: Basic Operations
05	Turning On/Off
05	Volume Control
05	Channel Selection
05	Transmission and Reception
06	Monitor
06	Scanning All Channels
07	LED Flashlight
07	Keypad Lock
07	Battery Save
07	Chapter 4: Menu Operations
07	CTCSS Tones / DCS Codes Selection
80	VOX Function
80	CALL Function
09	Roger Beep
09	Keypad Beep
10	Chapter 5: Troubleshooting
11	Chapter 6: Specification

Safety Information

Please read this information before using your radio. Failure to do so could result in personal injury, death, and/or damage to your radio, accessories and/or other property.

Radio Care

Caution

- Do not disassemble or modify the radio for any reason.
- Do not transmit while touching the antenna terminal or any exposed metallic parts of the aerial as this my result in burn.
- Please check and observe regulation in your country with regards to use whilst driving.

End of Life Disposal

• When the radio reaches the end of its useful life, please ensure that the unit is disposed of in an environmentally friendly way.

Battery Care

Precautions

- Turn the radio OFF before charging.
- Charge the battery pack before use.
- Do not recharge the battery pack if it is already fully charged as this will use one its charge cycles and may shorten its life.
- Charge the battery in accordance with the instructions enclosed with your charger.
- Do not charge the radio and/or battery pack if they are wet.

The battery pack includes potentially hazardous components. Please:

- Do not disassemble or reconstruct battery.
- Do not short-circuit the battery.
- Do not incinerate or apply heat to the battery.
- Do not immerse the battery in water or get it wet by other means.
- Do not charge the battery near fires or under direct sunlight.
- Use only the specified charger and observe charging requirements.
- Do not pierce the battery with any object or strike it with an instrument.
- Do not use the battery pack if it is damaged in any way.
- Do not reverse-charge or reverse-connect the battery.
- Do not touch a ruptured or leaking battery.

If liquids from the battery get on your skin or into your eyes, immediately:

- Wash your eyes out with fresh water avoiding rubbing them.
- Seek medical treatment.


Notes:

- If a battery is not to be used for an extended period of time (several months) remove the battery pack from the equipment and store in a cool and dry location part charged. Do not fully discharge the battery before storage.
- Each charge cycle reduces the battery's life. Minimize the number of times you charge your battery especially in hotter environments which further shorten a battery's life.

Radio Overview

Package Includes

- 2 x transceivers
- 2 x Li-ion battery packs
- 2 x AC adapters
- 2 x USB charging cables
- 2 x desktop chargers
- 2 x belt clips
- 2 x hand straps
- 2 x earpieces



LCD Display

- Selected channel
- 2. Selected code of CTCSS or DCS (CTCSS: 1-38 / DCS: 1-83)
- 3. CT/DCS: type of sub-audio tone selected
- 4. Battery status indicator
- 5. RSSI: TX/RX signal strength
- RX: radio in receive mode (busy channel)
 TX: radio in transmission (PTT pressed)
- Keypad lock activated
- 8. Duplex mode
- 9. High / low power selection in transmission
- 10. VOX function activated
- 11. SCAN function activated

Radio Part

- 12. Antenna
- 13. Built-in LED flashlight
- On/Off/Volume Knob: turn the radio ON or OFF and to adjust the radio's volume
- LED Indicator: solid red during transmission and solid green in reception
- ▲/▼ keys: to change the channel and settings in the menu
- Function key: short press this key to enter the radio's menu; long press it for about 3 seconds to activate the keypad lock
- 18. Built-in speaker
- 19. Built-in microphone
- PTT: press and hold down this key to transmit and talk, release it to receive and listen.
- 21. Up CALL / MON key: short press this key to send a call to the selected channel; long press it for about 2 seconds to activate Monitor function, that temporarily cuts off the squelch (for weak signals). This key can be disabled by programming software.

- 22. Down Flashlight / SCAN key: short press this key to activate the flashlight; long press it for about 2 seconds to activate the SCAN function. This key can be disabled by programming software.
- Audio Accessory Jack (Kenwood 2 Pin Connector)
 Connect compatible audio accessories, such as microphones, earpieces, etc
- 24. Rechargeable Li-ion battery pack
- 25. **USB port** for the recharge of the battery pack

Basic Operations

Turning On/Off

To turn on the radio, turn the **ON/OFF/VOLUME** knob clockwise until you hear it clicks, the LCD display will light up and the radio will play power up audio and channel number (if voice prompt feature is activated).

To turn off the radio, turn the knob counter-clockwise until you hear another click.

Volume Control

Turn the **VOLUME** knob to about half way and adjust it to a comfortable level as soon as you receive a signal. If you do not receive a signal you can use the up side **MON** key.

Channel Selection

Press the ▲/▼ keys to scroll up or down the channels till you select the desired channel.

Transmission and Reception

To transmit:

- 1. Make sure that no one else is currently talking on the selected channel.
- Keep PTT button firmly pressed. TX and RSSI icon will appear on the display.

- 3. Speak normally in the direction of the microphone.
- 4. When you have finished, release the **PTT. TX** and **RSSI** icon will disappear from the display.
- 5. When the radio is in reception mode (PTT not pressed) you will automatically receive any communication.

Note: during transmission and reception, as far as possible, try to keep the antenna in vertical position and to avoid obstacles towards the direction of the other party.

Monitor

The Monitor feature is for temporarily opening the squelch in order to listen to signals that are too weak to open the squelch. By opening the squelch you will listen the communication "chopped" by the squelch. In order to activate the Monitor function, so as to listen to all traffic on the selected channel, keep pressed the up side **CALL / MON** key for about 2 seconds. Keep pressed it again for about 2 seconds to disable this function.

Scanning All Channels

The radio can automatically search for signals throughout the bands by scanning, i.e. selecting the channels in sequence.

Long press the down side **Flashlight** / **SCAN** key for about 2 seconds to start scanning. When a signal is detected, the scanning pauses on that channel and you can transmit by pressing **PTT**. The **△**/**▼** keys allow you to change the direction of scanning (from lower channels to higher ones or vice versa) and therefore to skip communications which are of no interest.

If you want to stop it, long press the down side **Flashlight** / **SCAN** key for about 2 seconds again. The radio will go back to the channel from which the scanning originally started.

LED Flashlight

Shortly press the down side **Flashlight / SCAN** key to turn on/off the flashlight at the top of the radio.

Keypad Lock

Keep press **Function** key for about 3 seconds to activate keypad lock function and **6** will be displayed as confirmation. Only **PTT** key remain active. To disable this function, keep pressed again **Function** key for 3 seconds approx.

Battery Save

The battery saving feature enables a reduction in the consumption of up to 50%. Battery saving comes on automatically when the radio does not receive any signal for more than 5 seconds. When the batteries are discharged, replace the batteries or recharge the battery pack.

Menu Operations

CTCSS Tones / DCS Codes Selection

The radio can receive in two modes:

- a. Open traffic: in this case you will hear any communication transmitted on the selected channel.
- b. Group mode with CTCSS/DCS: CTCSS tones and DCS codes are access keys that allow you to receive only messages coming from parties using the same channel and code. The speaker will remain muted until the correct tone is received

To activate one of different 38 CTCSS tones & 83 DCS codes in RX and TX:

- 1. Select the desired channel.
- 2. Press the **Function** key once and the display shows "*OF*, *CT* & *DCS*" blinking.
- 3. By pushing the ▲/▼ keys the display will show CTCSS

(CT blinking) or DCS (dn blinking); press PTT to confirm the selection.

4. Press the **PTT** key again or wait for approximately 3 seconds to exit.

VOX Function

The radio enables hands free conversations through VOX function. You can enable it with or without accessories. The VOX sensitivity can be set in 9 different levels:

1 = high sensitivity (normal voice with no background noise) 9 = low sensitivity (useful in very noisy areas or if you talk loudly)

To activate VOX function:

- 1. Press the Function key till VOX will appear on the display.
- 2. Use the ▲/▼ keys to select the desired level.
- 3. Press PTT to confirm the selection.

To disable the VOX function, follow the instructions above and select option "OF".

CALL Function

FT-18 can send 10 different call tones. To send this audio signal to other users, press the up side **CALL / MON** key.

To select the desired call tone:

- 1. Press the Function key until the display shows "CA 1".
- 2. By pushing ▲/▼ keys you will hear the 10 pre-set melodies.
- 3. Confirm by pressing the PTT key.

Now, each time the radio sends out a tone call, it will beep with the selected melody.

Roger Beep

When your transmission is finished (PTT released), the radio gives out a sound that indicates to the other party that s/he can start talking. This function is enabled by default.

To deactivate it:

- 1. Press the **Function** key until the display shows "rb 2" blinking;
- Using the ▲/▼ keys select "of" and "rb of" will be displayed;
- 3. Press PTT button to confirm roger beep deactivation.

Keypad Beep

To deactivate the keypad beep, follow these steps:

- 1. Press the **Function** key until the display shows "bP on" blinking.
- Use the ▲/▼ keys until the display shows "bP of".
- 3. Confirm by pressing the PTT key.

Now you won't hear any beep at the pressure of any keys.

Troubleshooting

Problem	Possible Reasons and Potential Solutions					
No Power	Recharge or replace the battery pack;					
110 1 01101	Extreme operating temperatures may affect battery life.					
	Confirm CTCSS/DCS is set;					
Hearing other noises or	Frequency or CTCSS/DCS may be in use;					
conversation on a	Change settings: either change frequencies or					
channel	CTCSS/DCS on all radios;					
	Make sure the radio is at the right frequency and privacy					
	code when transmitting.					
Audio quality not good	Radio settings might not be matching up correctly.					
enough	Double check frequencies, CTCSS/DCS and bandwidths to make sure they are identical in all radios.					
-						
	Steel and/or concrete structures, heavy foliage, buildings or vehicles decrease range. Check for clear					
	line of sight to improve transmission;					
	Wearing radio close to body such as in a pocket or on a					
Limited talk range	belt decreases range;					
Limited talk range	Change location of radio. UHF radios provide great					
	coverage in industrial and commercial buildings.					
	Increasing power provides greater signal range and					
	increases penetration through obstructions.					
	Make sure the PTT button is completely pressed when					
	transmitting;					
	Confirm that the radios have the same channel,					
Can not transmitted or	frequency, private code and bandwidth settings;					
received	Recharge, replace and/or reposition batteries;					
	Obstructions and operating indoors, or in vehicles, may					
	interfere, change location;					
	Verify that the radio is not in Scan.					
11	Radios are too close, they must be at least seven feet					
Heavy static or interference	apart; Radios are too far apart or obstacles are interfering with					
interierence	transmission.					
	Recharge or replace the battery pack;					
Low battery	Extreme operating temperatures affect battery life.					
	Check that the radio/battery is properly inserted and					
Desktop Charger LED	check that the radio/battery is properly inserted and check the battery/charger contacts to ensure that they					
light does not blink	are clean and charging pin is inserted correctly.					
0 1 1 1 10	VOX feature might be set to OFF:					
Cannot activate VOX	Accessory not working or not compatible.					
	Check desktop charger is properly connected and					
Battery does not charge	correspond to a compatible AC adapter;					
battery does not charge	Check the charger's LED indicators to see if the battery					
	has a problem.					

Specifications

General

Frequency Range	446.00625 – 446.19375MHz
Channel Capacity	99 Channels
Channel Bandwidth	12 . 5KHz
Operating Voltage	3.7V DC
Dimensions (H x W x D)	90 x 52 x 30mm
Weight with battery	140g

Transmitter

RF Power(H/L)	500mW ERP
Frequency Stability	±1.5ppm
Spurious & Harmonics	-36dBm < 1GHz, -30dBm > 1GHz
FM Hum & Noise	≥ 36dB
Modulation Deviation	≤ 2.5KHz
Adjacent Channel Power	≥ 60dBC
Audio Frequency Response	+1 ~ -3dB
Audio Distortion	< 5%

Receiver

Sensitivity (12 dB SINAD)	≤ 0.3µV
Adjacent Channel Selectivity	≥ 60dBC
Audio Distortion	< 5%
Radiated Spurious Emissions	< -54dBm
Intermodulation Rejection	70 dB
Audio Output	1W @ 8 ohms

Hereby, we declare that our radio is in compliance with the essential requirements and other relevant provisions of RE Directive 2014/53/EU.

ADESSO